

PLIOGRIP® 7648B ADHESIVE
134669

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Ashland	Regulatory Information Number	1-800-325-3751
P.O. Box 2219	Telephone	614-790-3333
Columbus, OH 43216	Emergency telephone	1-800-ASHLAND (1-800-274-5263)

Product name	PLIOGRIP® 7648B ADHESIVE
Product code	134669
Product Use Description	No data

2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance: liquid, black

CAUTION! MAY BE HARMFUL IF SWALLOWED. MAY CAUSE ALLERGIC SKIN OR RESPIRATORY REACTION. MAY CAUSE EYE IRRITATION.

Potential Health Effects

Exposure routes

Inhalation, Skin absorption, Skin contact, Eye Contact, Ingestion

Eye contact

Can cause eye irritation. Symptoms include stinging, tearing, redness, and swelling of eyes.

Skin contact

May cause mild skin irritation. Symptoms may include redness and burning of skin. Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, and drying and cracking of skin, skin burns, and other skin damage.

Ingestion

Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful.

Inhalation

PLIOGRIP® 7648B ADHESIVE
134669

Breathing of vapor or mist is possible. Symptoms are not expected at air concentrations below the recommended exposure limits, if applicable (see Section 8.).

Aggravated Medical Condition

Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material:., lung (for example, asthma-like conditions)

Symptoms

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:., stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways), runny nose, Cough, sneezing, bronchitis, chest pain, Difficulty in breathing

Target Organs

Overexposure to this material (or its components) has been suggested as a cause of the following effects in humans:., effects on lung function

Carcinogenicity

This material is not listed as a carcinogen by the International Agency for Research on Cancer (IARC), the National Toxicology Program (NTP), or the Occupational Safety and Health Administration (OSHA). Carbon black has been shown to cause cancer in laboratory animals. The relevance of this finding to humans is uncertain. It is listed as a carcinogen by The International Agency for Research on Cancer (IARC). Epidemiological studies of the incidence of cancer, cardiovascular or respiratory disease in workers in the carbon black producing industry have shown no significant health effects due to occupational exposure to carbon black. This product may contain non-asbestiform talc. Inhalation of non-asbestiform talc has been shown to cause lung and adrenal cancer in female rats and adrenal gland cancer in male rats. It did not cause cancer in male or female mice similarly exposed. Talc is not listed as a carcinogen by the International Agency for Research on Cancer (IARC), the National Toxicology Program (NTP), or the Occupational Safety and Health Administration (OSHA).

Reproductive hazard

There are no data available for assessing risk to the fetus from maternal exposure to this material.

3. COMPOSITION/INFORMATION ON INGREDIENTS

PLIOGRIP® 7648B ADHESIVE
134669

Components	CAS-No.	Concentration
TALC	14807-96-6	>=20-<30%
CLAY	NJTS# 254504001-5594	>=1.5-<5%
AMORPHOUS SILICA	NJTS# 254504001-5608	>=1.5-<5%
CARBON BLACK	1333-86-4	>=0.1-<0.5%

4. FIRST AID MEASURES

Eyes

If symptoms develop, immediately move individual away from exposure and into fresh air. Flush eyes gently with water for at least 15 minutes while holding eyelids apart; seek immediate medical attention.

Skin

Remove contaminated clothing. Wash exposed area with soap and water. If symptoms persist, seek medical attention. Launder clothing before reuse.

Ingestion

Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

Inhalation

If symptoms develop, move individual away from exposure and into fresh air. If symptoms persist, seek medical attention. If breathing is difficult, administer oxygen. Keep person warm and quiet; seek immediate medical attention.

Notes to physician

Hazards: No information available.

Treatment: No information available.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Water spray, Dry chemical, Carbon dioxide (CO2)

Hazardous combustion products

PLIOGRIP® 7648B ADHESIVE
134669

toxic fumes, carbon dioxide and carbon monoxide, halogenated hydrocarbons, nitrogen oxides (NO_x)

Precautions for fire-fighting

Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively. Wear full firefighting turn-out gear (full Bunker gear), and respiratory protection (SCBA). DO NOT direct a solid stream of water or foam into hot, burning pools of liquid since this may cause frothing and increase fire intensity. Frothing can be violent and possibly endanger any firefighter standing too close to the burning liquid. Use water spray to cool fire exposed containers and structures until fire is out if it can be done with minimal risk. Avoid spreading burning liquid with water used for cooling purposes.

Flammability Class for Flammable Liquids

Combustible Liquid Class IIIB

6. ACCIDENTAL RELEASE MEASURES

Personal precautions

For personal protection see section 8. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

Environmental precautions

Prevent spreading over a wide area (e.g. by containment or oil barriers). Do not let product enter drains. Do not flush into surface water or sanitary sewer system.

Methods for cleaning up

Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. Stop spill at source, dike area of spill to prevent spreading, pump liquid to salvage tank. Remaining liquid may be taken up on sand, clay, earth, floor absorbent, or other absorbent material and shoveled into containers. Absorb liquid on vermiculite, floor absorbent or other absorbent material.

Other information

Comply with all applicable federal, state, and local regulations.

7. HANDLING AND STORAGE

Handling

PLIOGRIP® 7648B ADHESIVE
134669

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed.

Storage

Store in a cool, dry, ventilated area.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

TALC		14807-96-6	
ACGIH	time weighted average	2 mg/m3	Respirable fraction.
NIOSH	Recommended exposure limit (REL):	2 mg/m3	Respirable.
OSHA Z1A	time weighted average	2 mg/m3	Respirable dust.
Z3	time weighted average	0.1 mg/m3	Respirable.
Z3	time weighted average	0.3 mg/m3	Total dust.
US CA OEL	Time Weighted Average (TWA)	2 mg/m3	Respirable dust.
	Permissible Exposure Limit (PEL):		
ACGIH NIC	time weighted average	1 mg/m3	Respirable fraction.

General advice

These recommendations provide general guidance for handling this product. Personal protective equipment should be selected for individual applications and should consider factors which affect exposure potential, such as handling practices, chemical concentrations and ventilation. It is ultimately the responsibility of the employer to follow regulatory guidelines established by local authorities.

Exposure controls

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Eye protection

Wear chemical splash goggles when there is the potential for exposure of the eyes to liquid, vapor or mist.

Skin and body protection

To prevent repeated or prolonged skin contact, wear impervious clothing and boots. Wear resistant gloves such as:

PLIOGRIP® 7648B ADHESIVE
134669

Polyethylene

Respiratory protection

If workplace exposure limit(s) of product or any component is exceeded (see exposure guidelines), a NIOSH-approved air supplied respirator is advised in absence of proper environmental control. OSHA regulations also permit other NIOSH respirators (negative pressure type) under specified conditions (see your industrial hygienist). Engineering or administrative controls should be implemented to reduce exposure.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	liquid
Form	No data
Colour	black
Odour	No data
Boiling point/boiling range	No data
pH	No data
Flash point	(>)200.1 °F / 93.4 °C, Seta closed cup
Evaporation rate	No data
Explosion limits	No data
Vapour pressure	3.00 hPa @ 77 °F / 25 °C
Vapour density	No data
Density	1.26 g/cm ³ @ 77.00 °F / 25.00 °C 10.45 lb/gal @ 77.00 °F / 25.00 °C
Solubility	No data
Partition coefficient: n-octanol/water	No data
log Pow	no data available
Autoignition temperature	No data

10. STABILITY AND REACTIVITY

Stability
Stable.

Conditions to avoid
Exposure to moisture., heat

Incompatible products

PLIOGRIP® 7648B ADHESIVE
134669

alkalis, isocyanates, oxidizers, Strong acids

Hazardous decomposition products

Aldehydes, ketones, Organic acids, carbon dioxide and carbon monoxide, halogenated hydrocarbons, nitrogen oxides (NO_x)

Hazardous reactions

Product will not undergo hazardous polymerization.

Thermal decomposition

No data

11. TOXICOLOGICAL INFORMATION

Acute oral toxicity

TALC	no data available
CLAY	no data available
AMORPHOUS SILICA	LD 50 Rat: > 5,000 mg/kg
CARBON BLACK	LD 50 Rat: > 15,400 mg/kg

Acute inhalation toxicity

TALC	no data available
CLAY	no data available
AMORPHOUS SILICA	no data available
CARBON BLACK	no data available

Acute dermal toxicity

TALC	no data available
CLAY	no data available
AMORPHOUS SILICA	no data available
CARBON BLACK	LD 50 Rabbit: > 3 g/kg

12. ECOLOGICAL INFORMATION

Aquatic toxicity

Acute and Prolonged Toxicity to Fish

No data

Acute Toxicity to Aquatic Invertebrates

No data

PLIOGRIP® 7648B ADHESIVE
134669

AMORPHOUS SILICA	NJTS# 254504001-5608	none
CARBON BLACK	1333-86-4	none

	Health	Flammability	Reactivity	Other
HMIS	1*	1	0	
NFPA	1	1	0	

16. OTHER INFORMATION

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This MSDS has been prepared by Ashland's Environmental Health and Safety Department (1-800-325-3751).