

MATERIAL SAFETY DATA SHEET

Ashland

Page 001
 Date Prepared: 08/17/05
 Date Printed: 03/13/06
 MSDS No: 303.0407739-001.001

PLIOGRIP NVH FLEXIBLE FOAM PART A

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Material Identity

Product Name: PLIOGRIP NVH FLEXIBLE FOAM PART A
 Product Code: 599085
 General or Generic ID: POLURETHANE

Company

Ashland
 Ashland Distribution Co. &
 Ashland Specialty Chemical Co.
 P. O. Box 2219
 Columbus, OH 43216
 614-790-3333

Emergency Telephone Number:

1-800-ASHLAND (1-800-274-5263)
 24 hours everyday

Regulatory Information Number:

1-800-325-3751

2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient(s)	CAS Number	% (by weight)
METHYLENE DIPHENYLDIISOCYANATE	101-68-8	30.0- 60.0
POLYURETHANE PREPOLYMER	Trade Secret	10.0- 30.0
METHYLENE DIPHENYLISOCYANATE	26447-40-5	10.0- 30.0
POLYMERIC MDI	9016-87-9	5.0- 10.0

3. HAZARDS IDENTIFICATION

Potential Health Effects

Eye

Can cause eye irritation. Symptoms include stinging, tearing, redness, and swelling of eyes.

Skin

Can cause skin irritation. Symptoms may include redness and burning of skin, and other skin damage. Additional symptoms of skin contact may include: allergic skin reaction (delayed skin rash which may be followed by blistering, scaling and other skin effects), Passage of this material into the body through the skin is possible, but it is unlikely that this would result in harmful effects during safe handling and use.

Continued on next page

MATERIAL SAFETY DATA SHEET

Ashland

Page 002

Date Prepared: 08/17/05

Date Printed: 03/13/06

MSDS No: 303.0407739-001.001

PLIOGRIP NVH FLEXIBLE FOAM PART A

Swallowing

Swallowing this material may be harmful. Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful.

Inhalation

It is possible to breathe this material under certain conditions of handling and use (for example, during heating, spraying, or stirring). Breathing this material may be harmful. Symptoms usually occur at air concentrations higher than the recommended exposure limits (See Section 8).

Symptoms of Exposure

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: redness of the skin, skin rash, stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways), runny nose, cough, headache, chest pain, difficult breathing, lung edema (fluid buildup in the lung tissue), Exposure to this product (or a component) may cause an allergic reaction (narrowing of the air passages of the lungs resulting in difficult breathing, tightness in the chest, coughing and wheezing) in some sensitive individuals. Other symptoms of an allergic reaction may include itchy and watery eyes, runny and stuffy nose, sweating, flushing, hives, rapid heart rate, and lowered blood pressure.

Target Organ Effects

Overexposure to this material (or its components) has been suggested as a cause of the following effects in laboratory animals: nasal damage, lung damage, Overexposure to this material (or its components) has been suggested as a cause of the following effects in humans: skin sensitization, respiratory sensitization, effects on lung function.

Developmental Information

This material (or a component) has been shown to cause harm to the fetus in laboratory animal studies. Harm to the fetus occurs only at exposure levels that harm the pregnant animal. The relevance of these findings to humans is uncertain. Based on the available information, risk to the fetus from maternal exposure to this material cannot be assessed.

Continued on next page

MATERIAL SAFETY DATA SHEET

Ashland

Page 003

Date Prepared: 08/17/05

Date Printed: 03/13/06

MSDS No: 303.0407739-001.001

PLIOGRIP NVH FLEXIBLE FOAM PART A

Cancer Information

Based on the available information, this material cannot be classified with regard to carcinogenicity. In a two-year inhalation study in rats, exposure to polymeric methylene bisphenylisocyanate (MDI) aerosol caused a significant increase in benign (noncarcinogenic) lung tumors, along with a single carcinogenic lung tumor, at the highest dose only (6 mg/m³). The tumors occurred along with irritation of the respiratory tract and the accumulation of a yellow material in the lungs. There was irritation only at 1.0 mg/m³ and no effect at 0.2 mg/m³. MDI is not listed as carcinogenic by the International Agency for Research on Cancer (IARC), the National Toxicology Program (NTP) or the Occupational Safety and Health Administration (OSHA).

Other Health Effects

No data

Primary Route(s) of Entry

Inhalation, Skin absorption, Skin contact, Eye contact, Ingestion.

4. FIRST AID MEASURES

Eyes

If material gets into the eyes, immediately flush eyes gently with water for at least 15 minutes while holding eyelids apart. If symptoms develop as a result of vapor exposure, immediately move individual away from exposure and into fresh air before flushing as recommended above. Seek immediate medical attention. If symptoms develop, immediately move individual away from exposure and into fresh air. Flush eyes gently with water for at least 15 minutes while holding eyelids apart; seek immediate medical attention.

Skin

Remove contaminated clothing. Flush exposed area with large amounts of water. If skin is damaged, seek immediate medical attention. If skin is not damaged and symptoms persist, seek medical attention. Launder clothing before reuse. Remove contaminated clothing. Wash exposed area with soap and water. If symptoms persist, seek medical attention. Launder clothing before reuse.

Continued on next page

MATERIAL SAFETY DATA SHEET

Ashland

Page 004

Date Prepared: 08/17/05

Date Printed: 03/13/06

MSDS No: 303.0407739-001.001

PLIOGRIP NVH FLEXIBLE FOAM PART A

Swallowing

Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

Inhalation

If symptoms develop, immediately move individual away from exposure and into fresh air. Seek immediate medical attention; keep person warm and quiet. If person is not breathing, begin artificial respiration. If breathing is difficult, administer oxygen. If symptoms develop, move individual away from exposure and into fresh air. If symptoms persist, seek medical attention. If breathing is difficult, administer oxygen. Keep person warm and quiet; seek immediate medical attention.

Note to Physicians

Preexisting respiratory or allergic conditions may be aggravated in some individuals by exposure to fumes and gases. Pulmonary edema may be delayed. Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: respiratory tract, skin, lung (for example, asthma-like conditions).

5. FIRE FIGHTING MEASURES

Flash Point

> 300.0 F (148.8 C)

Explosive Limit

No data

Autoignition Temperature

No data

Hazardous Products of Combustion

May form: isocyanate vapors, toxic fumes, various hydrocarbons.

Continued on next page

MATERIAL SAFETY DATA SHEET

Ashland

Page 005

Date Prepared: 08/17/05

Date Printed: 03/13/06

MSDS No: 303.0407739-001.001

PLIOGRIP NVH FLEXIBLE FOAM PART A

Fire and Explosion Hazards

Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively.

Extinguishing Media

regular foam (such as AFFF), alcohol resistant (AR) foam, carbon dioxide, dry chemical.

Fire Fighting Instructions

Polymerization will take place under fire conditions. If polymerization occurs in a closed container, there is a possibility it will rupture violently. Cool storage container with water, if exposed to fire.

NFPA Rating

Health - 2, Flammability - 1, Reactivity - 1

6. ACCIDENTAL RELEASE MEASURES

Small Spill

Eliminate all sources of ignition such as flares, flames (including pilot lights), and electrical sparks. Absorb liquid on vermiculite, floor absorbent or other absorbent material. Persons not wearing proper personal protective equipment should be excluded from area of spill.

Large Spill

Prevent run-off to sewers, streams or other bodies of water. If run-off occurs, notify proper authorities as required, that a spill has occurred. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. Eliminate all ignition sources (flares, flames including pilot lights, electrical sparks).

7. HANDLING AND STORAGE

Handling

Precautions during use: avoid prolonged or frequently repeated skin contact with this material. Skin contact can be minimized by wearing impervious protective gloves. As with all products of this nature, good personal hygiene is essential. Hands and other exposed areas should be washed thoroughly with soap and water

Continued on next page

MATERIAL SAFETY DATA SHEET

Ashland

Page 006

Date Prepared: 08/17/05

Date Printed: 03/13/06

MSDS No: 303.0407739-001.001

PLIOGRIP NVH FLEXIBLE FOAM PART A

after contact, especially before eating and/or smoking. Regular laundering of contaminated clothing is essential to reduce indirect skin contact with this material. Warning. Sudden release of hot organic chemical vapors or mists from process equipment operating at elevated temperature and pressure, or sudden ingress of air into vacuum equipment, may result in ignitions without the presence of obvious ignition sources. Published "autoignition" or "ignition" temperature values cannot be treated as safe operating temperatures in chemical processes without analysis of the actual process conditions. Any use of this product in elevated temperature processes should be thoroughly evaluated to establish and maintain safe operating conditions.

Storage

Store in tightly closed containers. Do not allow moisture or water contamination of product. Contamination with water can cause dangerous pressure buildup in resealed containers. Do not reseal containers if contamination is suspected. Keep from freezing. Do not store near extreme heat, open flame, or sources of ignition.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eye Protection

Chemical splash goggles in compliance with OSHA regulations are advised; however, OSHA regulations also permit other type safety glasses. Consult your safety representative.

Skin Protection

Wear resistant gloves (consult your safety equipment supplier). To prevent repeated or prolonged skin contact, wear impervious clothing and boots.

Respiratory Protections

If workplace exposure limit(s) of product or any component is exceeded (see exposure guidelines), a NIOSH/MSHA approved air supplied respirator is advised in absence of proper environmental control. OSHA regulations also permit other NIOSH/MSHA respirators (negative pressure type) under specified conditions (see your industrial hygienist). Engineering or administrative controls should be implemented to reduce exposure.

Continued on next page

MATERIAL SAFETY DATA SHEET

Ashland

Page 007

Date Prepared: 08/17/05

Date Printed: 03/13/06

MSDS No: 303.0407739-001.001

PLIOGRIP NVH FLEXIBLE FOAM PART A

Engineering Controls

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV(s).

Exposure Guidelines

Component

METHYLENE DIPHENYLDIISOCYANATE (101-68-8)

OSHA PEL 0.020 ppm - Ceiling

OSHA VPEL 0.020 ppm - Ceiling

ACGIH TLV 0.005 ppm - TWA

POLYURETHANE PREPOLYMER

No exposure limits established

METHYLENE DIPHENYLISOCYANATE (26447-40-5)

No exposure limits established

POLYMERIC MDI (9016-87-9)

No exposure limits established

9. PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point

No data

Vapor Pressure

(for product) .000 @ F

Specific Vapor Density

No data

Specific Gravity

No data

Liquid Density

> 8.320 lbs/gal @ 68.00 F

> 8.320 lbs/gal @ 68.00 F

Continued on next page

MATERIAL SAFETY DATA SHEET

Ashland

Page 008

Date Prepared: 08/17/05

Date Printed: 03/13/06

MSDS No: 303.0407739-001.001

PLIOGRIP NVH FLEXIBLE FOAM PART A

Percent Volatiles

No data

Evaporation Rate

No data

Appearance

AMBER

State

LIQUID

Physical Form

LIQUID

Color

NO PIGMENT

Odor

WEAKLY AROMATIC

pH

No data

Freezing Point

58.0 - 68.0 F (14.4 - 20.0 C)

10. STABILITY AND REACTIVITY

Hazardous Polymerization

Product can undergo hazardous polymerization.

Hazardous Decomposition

May form: carbon dioxide and carbon monoxide, nitrogen oxides, various hydrocarbons.

Chemical Stability

Stable.

Continued on next page

MATERIAL SAFETY DATA SHEET

Ashland

Page 009

Date Prepared: 08/17/05

Date Printed: 03/13/06

MSDS No: 303.0407739-001.001

PLIOGRIP NVH FLEXIBLE FOAM PART A

Incompatibility

Avoid contact with: acids, alcohols, alkalis, aluminum, amines, iron, water, zinc.

11. TOXICOLOGICAL INFORMATION

This mixture has not been specifically tested.

12. ECOLOGICAL INFORMATION

No data

13. DISPOSAL CONSIDERATION

Waste Management Information

Destroy by liquid incineration. Dispose of in accordance with all applicable local, state and federal regulations. For assistance with your waste management needs - including disposal, recycling and waste stream reduction, contact Ashland Distribution Company, IC&S Environmental Services Group at 800-531-7106.

14. TRANSPORT INFORMATION

DOT Information - 49 CFR 172.101

DOT Description:

NON-REGULATED BY D.O.T.

Container/Mode:

55 GAL DRUM/TRUCK PACKAGE

NOS Component:

None

Continued on next page

MATERIAL SAFETY DATA SHEET

Ashland

Page 010

Date Prepared: 08/17/05

Date Printed: 03/13/06

MSDS No: 303.0407739-001.001

PLIOGRIP NVH FLEXIBLE FOAM PART A

RQ (Reportable Quantity) - 49 CFR 172.101

Product Quantity (lbs) Component

 11111 METHYLENE BISPHENOL ISOCYANATE (MDI)

15. REGULATORY INFORMATION

US Federal Regulations

TSCA (Toxic Substances Control Act) Status

TSCA (UNITED STATES) The intentional ingredients of this product are listed.

CERCLA RQ - 40 CFR 302.4(a)

Component	RQ (lbs)

METHYLENE BISPHENOL ISOCYANATE (MDI)	5000
--------------------------------------	------

SARA 302 Components - 40 CFR 355 Appendix A

None

Section 311/312 Hazard Class - 40 CFR 370.2

Immediate(X) Delayed(X) Fire() Reactive(X) Sudden
 Release of Pressure()

SARA 313 Components - 40 CFR 372.65

Section 313 Component(s)	CAS Number	%

METHYLENEBIS(PHENYLISOCYANATE) (MDI)	101-68-8	50.00
POLYMERIC DIPHENYLMETHANE DIISOCYANATE	9016-87-9	10.00

OSHA Process Safety Management 29 CFR 1910

None listed

EPA Accidental Release Prevention 40 CFR 68

None listed

International Regulations

Inventory Status

AICS (AUSTRALIA) The intentional ingredients of this product are listed.

DSL (CANADA) The intentional ingredients of this product are listed.

PICCS (PHILIPPINES) The intentional ingredients of this product are listed.

Continued on next page

MATERIAL SAFETY DATA SHEET

Ashland

Page 011

Date Prepared: 08/17/05

Date Printed: 03/13/06

MSDS No: 303.0407739-001.001

PLIOGRIP NVH FLEXIBLE FOAM PART A

State and Local Regulations

California Proposition 65

None

New Jersey RTK Label Information

METHYLENE BISPHENYL ISOCYANATE

101-68-8

Pennsylvania RTK Label Information

BENZENE, 1,1'-METHYLENEBIS[4-ISOCYANATO-

101-68-8

MATERIAL SAFETY DATA SHEET

Ashland

Page 001

Date Prepared: 08/15/05

Date Printed: 03/13/06

MSDS No: 303.0407740-001.001

PLIOGRIP NVH FLEXIBLE FOAM PART B

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Material Identity

Product Name: PLIOGRIP NVH FLEXIBLE FOAM PART B

Product Code: 599086

General or Generic ID: POLYOL MIXTURE

Company

Ashland
Ashland Distribution Co. &
Ashland Specialty Chemical Co.
P. O. Box 2219
Columbus, OH 43216
614-790-3333

Emergency Telephone Number:

1-800-ASHLAND (1-800-274-5263)
24 hours everyday

Regulatory Information Number:

1-800-325-3751

2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient (s)	CAS Number	% (by weight)
POLYOL MIXTURE		98.0-100.0

3. HAZARDS IDENTIFICATION

Potential Health Effects

Eye

May cause mild eye irritation. Symptoms include stinging, tearing, and redness.

Skin

Can cause skin irritation. Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, and drying and cracking of skin, burns and other skin damage.

Swallowing

Swallowing this material may be harmful.

Continued on next page

MATERIAL SAFETY DATA SHEET

Ashland

Page 002

Date Prepared: 08/15/05

Date Printed: 03/13/06

MSDS No: 303.0407740-001.001

PLIOGRIP NVH FLEXIBLE FOAM PART B

Inhalation

It is possible to breathe this material under certain conditions of handling and use (for example, during heating, spraying, or stirring).

Symptoms of Exposure

No data

Target Organ Effects

No data

Developmental Information

There are no data available for assessing risk to the fetus from maternal exposure to this material.

Cancer Information

This material is not listed as a carcinogen by the International Agency for Research on Cancer, the National Toxicology Program, or the Occupational Safety and Health Administration.

Other Health Effects

No data

Primary Route(s) of Entry

Inhalation, Skin contact, Eye contact, Ingestion.

4. FIRST AID MEASURES

Eyes

If symptoms develop, move individual away from exposure and into fresh air. Flush eyes gently with water while holding eyelids apart. If symptoms persist or there is any visual difficulty, seek medical attention.

Skin

Remove contaminated clothing. Wash exposed area with soap and water. If symptoms persist, seek medical attention. Launder clothing before reuse.

Continued on next page

MATERIAL SAFETY DATA SHEET

Ashland

Page 003

Date Prepared: 08/15/05

Date Printed: 03/13/06

MSDS No: 303.0407740-001.001

PLIOGRIP NVH FLEXIBLE FOAM PART B

Swallowing

Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

Inhalation

If symptoms develop, move individual away from exposure and into fresh air. If symptoms persist, seek medical attention. If breathing is difficult, administer oxygen. Keep person warm and quiet; seek immediate medical attention.

Note to Physicians

Preexisting respiratory or allergic conditions may be aggravated in some individuals by exposure to fumes and gases.

5. FIRE FIGHTING MEASURES

Flash Point

> 200.0 F (93.3 C)

Explosive Limit

No data

Autoignition Temperature

No data

Hazardous Products of Combustion

No data

Fire and Explosion Hazards

Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively.

Extinguishing Media

regular foam (such as AFFF), alcohol resistant (AR) foam, water fog, carbon dioxide, dry chemical.

Continued on next page

MATERIAL SAFETY DATA SHEET

Ashland

Page 004

Date Prepared: 08/15/05

Date Printed: 03/13/06

MSDS No: 303.0407740-001.001

PLIOGRIP NVH FLEXIBLE FOAM PART B

Fire Fighting Instructions

No data

NFPA Rating

Health - 1, Flammability - 1, Reactivity - 0

6. ACCIDENTAL RELEASE MEASURES

Small Spill

Eliminate all sources of ignition such as flares, flames (including pilot lights), and electrical sparks. Absorb liquid on vermiculite, floor absorbent or other absorbent material. Persons not wearing proper personal protective equipment should be excluded from area of spill.

Large Spill

Prevent run-off to sewers, streams or other bodies of water. If run-off occurs, notify proper authorities as required, that a spill has occurred. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. Eliminate all ignition sources (flares, flames including pilot lights, electrical sparks).

7. HANDLING AND STORAGE

Handling

Precautions during use: avoid prolonged or frequently repeated skin contact with this material. Skin contact can be minimized by wearing impervious protective gloves. As with all products of this nature, good personal hygiene is essential. Hands and other exposed areas should be washed thoroughly with soap and water after contact, especially before eating and/or smoking. Regular laundering of contaminated clothing is essential to reduce indirect skin contact with this material. Warning. Sudden release of hot organic chemical vapors or mists from process equipment operating at elevated temperature and pressure, or sudden ingress of air into vacuum equipment, may result in ignitions without the presence of obvious ignition sources. Published "autoignition" or "ignition" temperature values cannot be treated as safe operating temperatures in chemical processes without analysis of the actual process conditions. Any use of this product in elevated temperature processes should be

Continued on next page

MATERIAL SAFETY DATA SHEET

Ashland

Page 005

Date Prepared: 08/15/05

Date Printed: 03/13/06

MSDS No: 303.0407740-001.001

PLIOGRIP NVH FLEXIBLE FOAM PART B

thoroughly evaluated to establish and maintain safe operating conditions.

Storage

Do not store near extreme heat, open flame, or sources of ignition.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eye Protection

Chemical splash goggles in compliance with OSHA regulations are advised; however, OSHA regulations also permit other type safety glasses. Consult your safety representative.

Skin Protection

Wear resistant gloves (consult your safety equipment supplier). To prevent repeated or prolonged skin contact, wear impervious clothing and boots.

Respiratory Protections

Not required under normal conditions of use. If overexposure has been determined or documented, a NIOSH/MSHA jointly approved air supplied respirator is advised in absence of proper environmental control. OSHA regulations also permit other NIOSH/MSHA respirators under specified conditions. (See your safety equipment supplier.) Engineering or administrative controls should be implemented to reduce exposure.

Engineering Controls

Not required under normal conditions of use. However, if unusual operating conditions exist, then provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below PEL/TLV (s).

Exposure Guidelines

Component

POLYOL MIXTURE

No exposure limits established

Continued on next page

MATERIAL SAFETY DATA SHEET

Ashland

Page 006

Date Prepared: 08/15/05

Date Printed: 03/13/06

MSDS No: 303.0407740-001.001

PLIOGRIP NVH FLEXIBLE FOAM PART B

9. PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point

No data

Vapor Pressure

(for product) < .040 mmHg @ 68.00 F

Specific Vapor Density

No data

Specific Gravity

> 1.000 @ 68.00 F

Liquid Density

> 8.320 lbs/gal @ 68.00 F

> 8.320 lbs/gal @ 68.00 F

Percent Volatiles

No data

Evaporation Rate

No data

Appearance

VISCOUS

State

LIQUID

Physical Form

LIQUID

Color

No data

Odor

No data

Continued on next page

MATERIAL SAFETY DATA SHEET

Ashland

Page 007

Date Prepared: 08/15/05

Date Printed: 03/13/06

MSDS No: 303.0407740-001.001

PLIOGRIP NVH FLEXIBLE FOAM PART B

pH

No data

10. STABILITY AND REACTIVITY

Hazardous Polymerization

Product will not undergo hazardous polymerization.

Hazardous Decomposition

carbon dioxide and carbon monoxide, oxides of sulfur, nitrogen and phosphorus, various hydrocarbons.

Chemical Stability

Stable.

Incompatibility

Avoid contact with: strong acids, strong bases.

11. TOXICOLOGICAL INFORMATION

No data

12. ECOLOGICAL INFORMATION

No data

13. DISPOSAL CONSIDERATION

Waste Management Information

Destroy by liquid incineration. Dispose of in accordance with all applicable local, state and federal regulations.

Continued on next page

MATERIAL SAFETY DATA SHEET

Ashland

Page 008

Date Prepared: 08/15/05

Date Printed: 03/13/06

MSDS No: 303.0407740-001.001

PLIOGRIP NVH FLEXIBLE FOAM PART B

14. TRANSPORT INFORMATION

DOT Information - 49 CFR 172.101

DOT Description:

NON-REGULATED BY D.O.T.

Container/Mode:

55 GAL DRUM/TRUCK PACKAGE

NOS Component:

None

RQ (Reportable Quantity) - 49 CFR 172.101

Not applicable

15. REGULATORY INFORMATION

US Federal Regulations

TSCA (Toxic Substances Control Act) Status

TSCA (UNITED STATES) The intentional ingredients of this product are listed.

CERCLA RQ - 40 CFR 302.4(a)

None listed

SARA 302 Components - 40 CFR 355 Appendix A

None

Section 311/312 Hazard Class - 40 CFR 370.2

Immediate(X) Delayed() Fire() Reactive() Sudden
Release of Pressure()

SARA 313 Components - 40 CFR 372.65

None

OSHA Process Safety Management 29 CFR 1910

None listed

Continued on next page

MATERIAL SAFETY DATA SHEET

Ashland

Page 009

Date Prepared: 08/15/05

Date Printed: 03/13/06

MSDS No: 303.0407740-001.001

PLIOGRIP NVH FLEXIBLE FOAM PART B

EPA Accidental Release Prevention 40 CFR 68
None listed

International Regulations

Inventory Status

DSL (CANADA) The intentional ingredients of this product are listed.

State and Local Regulations

California Proposition 65

None